

# LED DRIVER CC/CV 250/350/700mA 3-20W PHASE-DIMMING

astro

## SPECIFICATION

TYPE:	Constant Current /Voltage
DRIVER CURRENT (mA):	250mA/350mA/700mA (CC)
DRIVER VOLTAGE (V):	12V (CV)
DIMMABLE:	LEADING/TRAILING EDGE
ELECTRICAL CLASS:	Class II
SUPPLY VOLTAGE (V):	220-240V AC
SUPPLY FREQUENCY (Hz):	50/60
POWER FACTOR:	0.85
MIN. OUTPUT VOLTAGE (V DC):	15/10/5V DC (CC)
MAX. OUTPUT VOLTAGE (V DC):	48/48/29V DC (CC)
MIN. OUTPUT POWER (W):	3
MAX. OUTPUT POWER(W):	20W (CC) /11W (CV)
INRUSH CURRENT(A):	5A for 50 $\mu$ s
IP RATING:	IP20
WORKING TEMPERATURE (°C):	-25 - +40
CONNECTION TYPE:	SCREW TERMINALS
LENGTH (mm):	108
WIDTH (mm):	52
HEIGHT (mm):	22
MIN. CIRCULAR APERTURE (mm/inch):	57mm/2-1/4"
MAX. LED DISTANCE (m):	2
MANUFACTURER:	TCI
MODEL NUMBER:	DC MINI JOLLY MD 20



CODE: 6008081

Wire constant current LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.