




**Mode**

**TC-0073-BLA**

Downlight IP23 Mode LED 5.4 LED warm-white 3000K ON-OFF White 605

**TECHNICAL FEATURES**



Luminaire total power : 5.4W

Real lumens : 409

Nominal lumens : 605

Real lm/W : 76

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Lens / reflector angle : MEDIUM 37°

UGR : <= 19

Structure material : Polycarbonate

Structure finish : White

Diffuser material : Polycarbonate

Diffuser finish : Sandblasted

Voltage / frequency : 100-240V/50-60Hz

Dimming protocol : ON-OFF

Power Factor : 0.49

Useful life : 36.000h L70B30

Warranty : 5 Years

**LUMINOTECHNIC FEATURES**

TM30 RG: 96

TM30 RF: 90

Melanopic ratio: 0.55

CRI: 90

MacAdam steps: 3

Photobiological risk: RG1

UGR

UGR crosswise: 18.1

UGR lengthwise: 18.1

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	18.1
UGR lengthwise	18.1

Lampholder	Quantity	Light source power (W)
LED	1	5.4W

**LOGISTICS**

Net weight (kg): 0.11

Packaged weight (kg): 0.2

